

INT

STD

DE

## Arenalux® - Bronze Frost - Decorative Effect Diffuision®

<b>Visible Light Transmittance</b>		<b>53%</b>
transmission de la lumière visible (FRA)	luce visibile trasmessa (ITA)	
transmission de luz visible (SPA)	licht durchlass (GER)	
<b>Solar Transmittance</b>		<b>62%</b>
energie solaire transmise (FRA)	energia solare trasmessa (ITA)	
energia solar transmitida (SPA)	sonnenenergie durchlass (GER)	
<b>Solar Reflectance</b>		<b>14%</b>
energie solaire réfléchie (FRA)	energia solare riflessa (ITA)	
energia solar reflejada (SPA)	sonnenenergie reflektion (GER)	
<b>Solar Absorbance</b>		<b>24%</b>
energie solaire absorbée (FRA)	energia solare assorbita (ITA)	
energia solar absorbida (SPA)	sonnenenergie absorbtion (GER)	
<b>Winter U-Value</b>		<b>1,09</b>
u-value facteur (FRA)	fattore-u (ITA)	
u-valor factor (SPA)	u-faktor (GER)	
<b>UV Rejected</b>		<b>99%</b>
u.v. rejetés (FRA)	u.v. respinti (ITA)	
u.v. repelidos (SPA)	u.v. reflektion (GER)	
<b>Glare Reduction</b>		<b>18%</b>
riduction de l'éblouissement (FRA)	riduzione dell'abbagliamento (ITA)	
reduccion de la intensidad de luz (SPA)	blendungsreduktion (GER)	
<b>Shading Coefficient</b>		<b>0,81</b>
coefficient d'ombrage (FRA)	coefficiente d'ombreggiatura (ITA)	
coeficiente de sombreado (SPA)	schattierungskoeffizient (GER)	
<b>Total Solar Energy Rejected - TSER</b>		<b>38%</b>
total energie solaire rejetée (FRA)	energia solare totale respinta (ITA)	
energía total rechazada (SPA)	gesamte reflektierte solarenergie (GER)	
<b>Solar Heat Gain Coefficient - SHGC</b>		<b>62%</b>
facteur solaire (FRA)	fattore solare (ITA)	
factor solar (SPA)	gesamtenergie durchlassgrad (GER)	
<b>Film Thickness (micron)</b>		<b>50</b>
epaisseur (FRA)	spessore (ITA)	
espesor (SPA)	dicke (GER)	
<b>Structure</b>		<b>2 ply</b>
structure (FRA)	struttura (ITA)	
estructura (SPA)	struktur (GER)	
<b>Peel Strength (pi)</b>		<b>NA</b>
résistance au décollement (FRA)	resistenza al distaccamento (ITA)	
resistencia al desprendimiento (SPA)	schale stärke (GER)	
<b>Tensile Strength (psi)</b>		<b>NA</b>
résistance à la traction (FRA)	resistenza alla trazione (ITA)	
fuerza de tension (SPA)	zerreiβfestigkeit (GER)	

ARENA 2-80 BRO

Bronze Frost  
2 Ply - Interior use

[www.astilla.com](http://www.astilla.com)  
[info@astilla.com](mailto:info@astilla.com)

MEMBER OF  
**IWFA**  
 International Window  
 Film Association